


MG200 series



select	Inquiry	Type	Style	(d) Bore Diameter	(D) Outer Diameter	(W2) Inner Ring	(W1) Outer Ring	(R) Radius	(r) Fillet	(C) Dynamic Load	(Co) Static Load
MG-205-FF	1	25 mm 0.9843 in	2.5630 in	.5890 in	.8380 in	.2460 in	.0590 in	14010 N 3150 lb	7830 N 1760 lb		
MG-206-FF	3	30 mm 1.1811 in	3.235 in	.7712 in	1.0000 in	N/A	.0400 in	19491 N 4380 lb	11255 N 2530 lb		
MG-206-FFA	3	30 mm 1.1811 in	3.2000 in	.7712 in	1.0000 in	N/A	.0400 in	19490 N 4380 lb	11255 N 2530 lb		
MG-206-FFB	1	30 mm 1.1811 in	3.0000 in	.6299 in	1.0620 in	.0625 in	.0400 in	19490 N 4380 lb	11255 N 2530 lb		
MG-206-FFB	1	30 mm 1.1811 in	3.0000 in	.6299 in	1.0620 in	.0625 in	.0400 in	19490 N 4380 lb	11255 N 2530 lb		
MG-206-FFE	1	30 mm 1.1811 in	3.0000 in	.6299 in	1.1250 in	.0625 in	.0400 in	19490 N 4380 lb	11255 N 2530 lb		
MG-206-FFE	1	30 mm 1.1811 in	3.0000 in	.6299 in	1.1250 in	.0625 in	.0400 in	19490 N 4380 lb	11255 N 2530 lb		
MG-206-FFH	2A	30 mm 1.1811 in	3.1300 in	.6530 in	1.1250 in	.2500 in	.0400 in	27360 N 6150 lb	18860 N 4240 lb		
MG-206-FFHA	2A	30 mm 1.1811 in	3.1300 in	.6530 in	1.1250 in	.2500 in	.0400 in	27360 N 6150 lb	18860 N 4240 lb		
MG-206-FFK	2A	30 mm 1.1811 in	3.4000 in	.6530 in	1.1250 in	.2500 in	.0400 in	27360 N 6150 lb	18860 N 4240 lb		
MG-206-FFKA	2A	30 mm 1.1811 in	3.4000 in	.6530 in	1.1250 in	.2500 in	.0400 in	27360 N 6150 lb	18860 N 4240 lb		
MG-206-FFM	4A	30 mm 1.1811 in	3.2000 in	.7712 in	1.0000 in	N/A	.0400 in	27360 N 6150 lb	18860 N 4240 lb		

MG200 series

MG-206-FFP	2A	30 mm1.1811 in	3.4700 in	.6530 in	1.1520 in	.2360 in	.0400 in	27360 N6150 lb	18860 N4240 lb	
MG-206-FFPA	2A	30 mm1.1811 in	3.4855 in	.6530 in	1.1520 in	.2360 in	.0400 in	27360 N6150 lb	18860 N4240 lb	
MG-206-FFPB	2A	30 mm1.1811 in	3.5055 in	.6530 in	1.1520 in	.2360 in	.0400 in	27360 N6150 lb	18860 N4240 lb	
MG-206-FFU	2A	30 mm1.1811 in	3.1940 in	.6530 in	1.1520 in	.2360 in	.0400 in	27360 N6150 lb	18860 N4240 lb	
MG-206-FFUA	2A	30 mm1.1811 in	3.2140 in	.6530 in	1.1520 in	.2360 in	.0400 in	27360 N6150 lb	18860 N4240 lb	
MG-206-FFUB	2A	30 mm1.1811 in	3.2340 in	.6530 in	1.1520 in	.2360 in	.0400 in	27360 N6150 lb	18860 N4240 lb	
MG-206-FFW	2A	30 mm1.1811 in	3.4140 in	.6530 in	1.1250 in	.1900 in	.0400 in	27360 N6150 lb	18860 N4240 lb	
MG-206-FFWA	2A	30 mm1.1811 in	3.4440 in	.6530 in	1.1250 in	.1900 in	.0400 in	27360 N6150 lb	18860 N4240 lb	
MG-206-FFWB	2A	30 mm1.1811 in	3.4740 in	.6530 in	1.1250 in	.1900 in	.0400 in	27360 N6150 lb	18860 N4240 lb	
MG-206-FFZ	2A	30 mm1.1811 in	3.1390 in	.6530 in	1.1250 in	.1900 in	.0400 in	27360 N6150 lb	18860 N4240 lb	
MG-206-FFZA	2A	30 mm1.1811 in	3.1690 in	.6530 in	1.1250 in	.1900 in	.0400 in	27360 N6150 lb	18860 N4240 lb	
MG-206-FFZB	2A	30 mm1.1811 in	3.1990 in	.6530 in	1.1250 in	.1900 in	.0400 in	27360 N6150 lb	18860 N4240 lb	
MG-207-FFA	8	35 mm1.3780 in	3.2230 in	.6743 in	1.0670 in	.1250 in	.0400 in	38930 N8750 lb	26780 N6020 lb	
MG-207-FFB	7	35 mm1.3780 in	3.4800 in	.6693 in17 mm	1.2550 in	.0625 in	.0400 in	25670 N5770 lb	15300 N3440 lb	
MG-207-FFH	6A	35 mm1.3780 in	2.5920 in	.8268 in21 mm	1.2550 in	N/A	.0400 in	38930 N8750 lb	26780 N6020 lb	
MG-207-FFJ	6A	35 mm1.3780 in	3.5920 in	.7874 in20 mm	1.2550 in	N/A	.0400 in	38930 N8750 lb	26780 N6020 lb	
MG-207-FFJA	2A	35 mm1.3780 in	3.6190 in	.7860 in	1.2550 in	.3100 in	.0400 in	38930 N8750 lb	26780 N6020 lb	

MG200 series

MG-207-FFJB	1	35 mm1.3780 in	3.7250 in	.6693 in17 mm	0.9960 in	.3120 in	.0400 in	25670 N5770 lb	15300 N3440 lb	
-------------	---	----------------------	--------------	---------------------	--------------	-------------	-------------	----------------------	----------------------	--