


# MG300 series



select	Inquiry	Type	Style	(d) Bore Diameter	(D) Outer Diameter	(W2) Inner Ring	(W1) Outer Ring	(R) Radius	(r) Fillet	(C) Dynamic Load	(Co) Static Load
MG-305-DD	1	25 mm 0.9843 in	3.0000 in	.6693 in 17 mm	1.0000 in	.3000 in	.0400 in	20510 N 4610 lb	11120 N 2500 lb		
MG-305-DD	1	25 mm 0.9843 in	3.0000 in	.6693 in 17 mm	1.0000 in	.3000 in	.0400 in	20510 N 4610 lb	11120 N 2500 lb		
MG-305-DDA	1	1.0000 in	2.9370 in	.6693 in 17 mm	1.0000 in	.3300 in	.0400 in	20510 N 4610 lb	11120 N 2500 lb		
MG-305-DDA	1	1.0000 in	2.9370 in	.6693 in 17 mm	1.0000 in	.3300 in	.0400 in	20510 N 4610 lb	11120 N 2500 lb		
MG-305-DDB	1B	25 mm 0.9843 in	3.0000 in	.6693 in 17 mm	1.0000 in	.2500 in	.0400 in	20510 N 4610 lb	11120 N 2500 lb		
MG-305-DDE	1	25 mm 0.9843 in	3.1320 in	.6680 in	.9450 in	.2360 in	.0980 in	20510 N 4610 lb	11120 N 2500 lb		
MG-305-DDE	1	25 mm 0.9843 in	3.1320 in	.6680 in	.9450 in	.2360 in	.0980 in	20510 N 4610 lb	11120 N 2500 lb		
MG-306-DD	1	30 mm 1.1811 in	3.5000 in	.7480 in 19 mm	1.0000 in	.3750 in	.0400 in	26600 N 5980 lb	14900 N 3350 lb		
MG-306-DDB	1	30 mm 1.1811 in	3.2500 in	.7480 in 19 mm	1.0620 in	.3430 in	.0400 in	26600 N 5980 lb	14900 N 3350 lb		
MG-306-FF	1	30 mm 1.1811 in	3.5000 in	.7480 in 19 mm	1.0000 in	.3750 in	.0400 in	26600 N 5980 lb	14900 N 3350 lb		
MG-306-FF	1	30 mm 1.1811 in	3.5000 in	.7480 in 19 mm	1.0000 in	.3750 in	.0400 in	26600 N 5980 lb	14900 N 3350 lb		
MG-306-FFB	1	30 mm 1.1811 in	3.2500 in	.7480 in 19 mm	1.0620 in	.3430 in	.0400 in	26600 N 5980 lb	14900 N 3350 lb		
MG-306-FFB	1	30 mm 1.1811 in	3.2500 in	.7480 in 19 mm	1.0620 in	.3430 in	.0400 in	26600 N 5980 lb	14900 N 3350 lb		

MG300 series

MG-307-FFA	1	35 mm1.3780 in	4.0000 in	.8268 in21 mm	1.1250 in	.3750 in	.0590 in	33330 N7490 lb	19130 N4300 lb
MG-307-FFA	1	35 mm1.3780 in	4.0000 in	.8268 in21 mm	1.1250 in	.3750 in	.0600 in	33330 N7490 lb	19130 N4300 lb
MG-307-FFB	7	35 mm1.3780 in	3.9800 in	.8268 in21 mm	1.2550 in	.1250 in	.0600 in	33330 N7490 lb	19130 N4300 lb
MG-307-FFE	5	35 mm1.3780 in	3.9900 in	.8268 in21 mm	1.1250 in	N/A	.0600 in	33330 N7490 lb	19130 N4300 lb
MG-307-FFH	1	35 mm1.3780 in	3.9900 in	.8268 in21 mm	1.1250 in	.3700 in	.0600 in	33330 N7490 lb	19130 N4300 lb
MG-307-FFHA	1	35 mm1.3780 in	4.0150 in	.8268 in21 mm	1.1250 in	.3750 in	.0590 in	33330 N7490 lb	19130 N4300 lb
MG-307-FFJ	1	35 mm1.3780 in	3.7250 in	.8268 in21 mm	1.0000 in	.3750 in	.0600 in	36890 N8290 lb	20380 N4580 lb
MG-307-FFK	1	35 mm1.3780 in	3.7250 in	.8268 in21 mm	1.0000 in	.3750 in	.0600 in	33330 N7490 lb	19130 N4300 lb
MG-307-FFM	1B	35 mm1.3780 in	3.9930 in	.8268 in21 mm	1.1250 in	.2400 in	.0600 in	33330 N7490 lb	19130 N4300 lb
MG-307-FFP	1B	35 mm1.3780 in	3.9900 in	.8268 in21 mm	1.1250 in	.2760 in	.0600 in	33330 N7490 lb	19130 N4300 lb
MG-307-FFQ	4	35 mm1.3780 in	4.4900 in	N/A	1.2550 in	.2500 in	.0400 in	33330 N7490 lb	19130 N4300 lb
MG-307-FFQB	4	35 mm1.3780 in	4.4900 in	N/A	1.2550 in	.1250 in	.0400 in	33330 N7490 lb	19130 N4300 lb
MG-307-FFWR	1	35 mm1.3780 in	3.7550 in	.8268 in21 mm	0.9960 in	.3150 in	.0600 in	33330 N7490 lb	19130 N4300 lb
MG-307-FFZ	2	35 mm1.3780 in	4.0000 in	.8268 in21 mm	1.1250 in	.3750 in	.0600 in	52640 N11830 lb	34530 N7760 lb
MG-307-LL	1C	35 mm1.3780 in	3.6170 in	.7874 in20 mm	1.2250 in	.3100 in	.0600 in	33330 N7490 lb	19130 N4300 lb
MG-307-LLA	1C	35 mm1.3780 in	3.2230 in	.7874 in20 mm	1.2250 in	.3100 in	.0600 in	33330 N7490 lb	19130 N4300 lb
MG-307-LLB	1C	35 mm1.3780 in	3.2300 in	.7874 in20 mm	1.2250 in	.3100 in	.0600 in	33330 N7490 lb	19130 N4300 lb